

BrushHound Front Brush Shredder



RockHound

ATTACHMENTS



Mulch & Shred

Heavy Material Quickly

The RockHound, BrushHound FH series is designed to effectively cut & mulch heavy vegetation with standard flow or high flow power units. Front mounted with a universal skid steer style mounting plate. Discharge is down so no debris is thrown in the operators station. This BrushHound is available in 5, 6 and 7 foot widths with hydraulic drive. Double wall construction and recutter bar standard. Front chain debris curtain & drive guard protector standard.



Features

- Electronically balanced for smooth operation
- Long life replaceable internal liners standard
- Gear type hydraulic motor with motor protection
- High strength 1/2" & 3/8" steel plate construction
- Reversible 2.25 pound flail knives
- Adjustable rear ground roller height control
- Unique castlenut roll pin blade retention system
- Optional / replaceable side skid shoes

Specifications

| | Model 60F-H | Model 72F-H | Model 84F-H |
|---------------------|--------------------|--------------------|--------------------|
| Working Width | 60"(152.4 cm) | 72" (182.8 cm) | 84" (213.3 cm) |
| Overall Width | 72"(182.8 cm) | 84" (213.3 cm) | 96" (243.8 cm) |
| Weight | 1475 lbs (669kg) | 1625lbs (737kg) | 1850lbs (839kg) |
| Cutting Height | 0-6" (0-15.2 cm) | 0-6" (0-15.2 cm) | 0-6" (0-15.2 cm) |
| Number of knives | 32 HD flail knives | 40 HD flail knives | 48 HD flail knives |
| Capacity | 5". (12.7cm) | 4". (10.6 cm) | 3". (7.62 cm.) |
| HP required | 30-60+ hp | 30-60+ hp | 30-60+ hp |
| GPM recommendations | 16-20 gpm | 18-30 gpm | 20-40 gpm |

NOTE: Consult your power unit's manual to insure lift capacities are not exceeded. "all models come standard with heavy duty skid steer style mounting plate but custom mounts are available. Call for pricing. Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place. Design, materials and/or specifications are subject to change without notice and without liability therefore. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas. © 2011 RockHound Attachments. Visit our website at www.rockhound.com Or, call toll-free: 1-800-426-5615 PRINTED IN U.S.A.

RockHound Attachments

PO Box 220 Hughson, California 95326

Toll Free: 800-426-5615 Fax: 360-230-2322

E-mail: info@rockhound.com Visit our web site at: www.rockhound.com